


# LGMG Electric - Articulating Boom Lift


## **SPECIFICATIONS**


Measurements         Metric         Imperial           Work Height Max.         15m         49'3"           Platform Height Max.         13m         42'8"           Horizontal Outreach         7.46m         24'6"           Up and Over Height         7.1m         23'4"           Platform Length         1.2m         3'11"           Platform Width         0.9m         2'11"           Stowed Length         6.7m         22'           Length-Transport (jib tucked)         5.76m         18'11"           Overall Width         1.5m         4'11"           Stowed Height         1.98m         6'6"           Height-Transport         2.66m         8'9"           Wheelbase         2.03m         6'8"	
Platform Height Max.       13m       42'8"         Horizontal Outreach       7.46m       24'6"         Up and Over Height       7.1m       23'4"         Platform Length       1.2m       3'11"         Platform Width       0.9m       2'11"         ♠ Stowed Length       6.7m       22'         Length-Transport (jib tucked)       5.76m       18'11"         ♠ Overall Width       1.5m       4'11"         ♠ Stowed Height       1.98m       6'6"         Height-Transport       2.66m       8'9"	
Horizontal Outreach  Up and Over Height  7.1m  23'4"  Platform Length  1.2m  3'11"  Platform Width  0.9m  2'11"  Stowed Length  6.7m  22'  Length-Transport (jib tucked)  5.76m  18'11"  Overall Width  1.5m  4'11"  Stowed Height  1.98m  6'6"  Height-Transport  2.66m  8'9"	
Up and Over Height       7.1m       23'4"         Platform Length       1.2m       3'11"         Platform Width       0.9m       2'11"         Stowed Length       6.7m       22'         Length-Transport (jib tucked)       5.76m       18'11"         Overall Width       1.5m       4'11"         Stowed Height       1.98m       6'6"         Height-Transport       2.66m       8'9"	
Platform Length         1.2m         3'11"           Platform Width         0.9m         2'11"           Stowed Length         6.7m         22'           Length-Transport (jib tucked)         5.76m         18'11"           Overall Width         1.5m         4'11"           Stowed Height         1.98m         6'6"           Height-Transport         2.66m         8'9"	
Platform Width         0.9m         2'11"           Stowed Length         6.7m         22'           Length-Transport (jib tucked)         5.76m         18'11"           Overall Width         1.5m         4'11"           Stowed Height         1.98m         6'6"           Height-Transport         2.66m         8'9"	
<ul> <li>Stowed Length 6.7m 22'</li> <li>Length-Transport (jib tucked) 5.76m 18'11"</li> <li>Overall Width 1.5m 4'11"</li> <li>Stowed Height 1.98m 6'6"</li> <li>Height-Transport 2.66m 8'9"</li> </ul>	
Length-Transport (jib tucked) 5.76m 18'11"  3 Overall Width 1.5m 4'11"  4'11"  Stowed Height 1.98m 6'6"  Height-Transport 2.66m 8'9"	
<ul> <li>Overall Width</li> <li>Stowed Height</li> <li>Height-Transport</li> <li>1.5m</li> <li>4'11"</li> <li>6'6"</li> <li>8'9"</li> </ul>	
Stowed Height 1.98m 6'6" Height-Transport 2.66m 8'9"	
Height-Transport 2.66m 8'9"	
<b>1</b> Wheelbase 2.03m 6'8"	
Ground Clearance 0.2m 8"	
PRODUCTIVITY	
Max. Platform Occupancy 2	
Platform Capacity 200kg 440 lbs	
Turntable Rotation 355° 355°	
Drive Speed-Stowed 5km/h 3.1mph	
Drive Speed-Raised 0.8km/h 0.5mph	
Gradeability 30% 30%	
Max. Wind Speed 12.5m/s 28mph	
Turning Radius-Inside 2.2m 7'3"	
Turning Radius-Outside 4.07m 13'4"	
Max.Slope 3°/3° 3°/3°	
Tires Type Solid Non-marking	
Tires Models 600x190	
Ground Pressure, Tyres /	
POWER	
Lead-acid Battery 48V(8x6V),330Ah,AGM	
Lithium Battery (A13JE-Li) 48V 250Ah	
HYDRAULIC SYSTEM	
Hydraulic Oil Volume 25L 6.6gal	
WEIGHT	
Machine Weight (CE/ANSI) 6,950kg 15,322 lbs	


STANDARD FEATURES		
Proportional control	Anti-collision protection	
Horn/Hour meter	Auto-leveling platform	
AC drive motor	Intelligent diagnostic system	
Drop bar entry	Over tilt protection system	
Power switch	Overload sensing system	
Full-height drive	Descent alarm with flashing beacon	
Telematics connector	Solid non-marking tires	

OPTIONAL	
AC power to platform	Biodegradable hydraulic oil
Telematics	









Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

## LINGONG HEAVY MACHINERY CO., LTD.

Address: No. 2676, Kejia Road, Jinan, Shandong, China Email: sales@lgmg.com.cn Tel: +86 531 6787 9283

#### LGMG Europe B.V.

Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands Email: sales@lgmgeurope.com Tel: +31 850 642 777

### LGMG North America Inc.

Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States Email: sales@lgmgna.com Tel: +1 833 288 5464



